

- Flat-Free Caster Wheels Standard
- Integrated Tie Down Points
- Multiple Cutting Height-Easily Adjustable
- Heavy Duty Construction

- 3 Heavy Duty Blades Cuts without Windrowing
- Easy Connect Hood Design
- Out-Front Deck for Excellent Visibility
- Cuts Material Before Driving Over



TOUGH CUT

Model	HQ682
Stock Code	39.55118
Width of Cut	68 inches (173 cm)
Number of Blades/Type	3 blades, 5/16 x 2½ x 23 inches (79mm x 6.35cm x 58cm)
Cutting Height (with Swivel Wheels Removed)	3 – 4¼ inches
Cutting Height	31/2 - 7 inches (89 to 178 mm)
Deck Construction	Multi Gauge, 5/16 inch (7.9 mm) at spindle mount
Spindles/Pulleys	Field Serviceable w/ Top Grease Fittings
Optional Accessory	1
Swivel Wheel Kit	70.8213
Dimensions	
Length	59 inches (150 cm)
Width	69 inches (175 cm)
Height	22 inches (56 cm)
Weight	475 lbs (215.5 kg)

All specifications subject to change without notice or obligation

STANDARD FEATURES

- •Rear Adjustment for Deck Pitch
- Heavy Duty Blades
- •Tilt-Up Deck
- Ventrac Mount System
- •Front Castor Wheels

OPTIONAL ACCESSORIES

•Flip Up Kit



The HQ682 **Tough Cut Mower** is the mower of choice for mowing high grass, thick weeds, and heavy brush. A large baffled front opening assists in directing materials into the deck and helps hinder debris from escaping. Three heavy-duty blades counter rotate to cut and deposit waste evenly without windrowing. Capable of tackling saplings and large thorn bushes, the Tough Cut makes short work out of overgrown thickets.

The HQ682 comes with front caster wheels as a standard feature. Four tie-down points have been added for secure trailering.

The Tough Cut has three adjustable cutting heights: 3, 3 5/8, and 4¼ inches. Easy servicing of belts and pulleys is provided by the hinged and removable cover. The manual tilt-up deck provides access under the deck. A hydraulic flip-up kit is available as an option for easier access to the underside of the deck for cleaning and blade replacement.



