

- Mow and Collect in One Pass
- Collects Up to 16 cu ft

- Collection Bin Rises 60"
- 10hp Independent Engine

# **VACUUM COLLECTION SYSTEM**

Model	RV602
Stock Code	39.55361
Collection Bin Capacity	13 cu ft recommended; 16 cu ft maximum
Lift Capacity	300 lbs (136 kg)
Bin Lifting Height	60 inches (152 cm)
Lifting Time	5 seconds
Lowering Time	4 seconds
Fan Blades	5
Hose Diameter	8 inches (20.3 cm)
Engine	B&S Vanguard Model 19, 10HP, 3600RPM, single cylinder, horizontal shaft

MS600 Collection Boot	70.8169
MS720 and MT720 Collection Boot	70.8169

# **Hydraulic Requirements**

(choose one)	4100/4200	4500
3 Point Hitch Kit	70.4063	70.4100
Rear Hydraulic Valve (Required W/O 3pt Hitch)	70.4088	70.4126

## **Optional Accessory**

Docking Station	70.8092
Dimensions	
Lenath	40 inches (102 cm)

Length			40 inches (102 cm)
Width			65 inches (165 cm)
Height			53 inches (135 cm)
Weight			525 lbs (238 kg)

All specifications subject to change without notice or obligation





The Ventrac RV602 Vacuum Collection System is for grass and leaf collection, and it consists of three primary components:

- 1. The bin assembly mounts to the rear of select Ventrac 4500 + 4100 + 4200 tractors
- 2. The suction/blower system powered by a 10HP B&S Vanguard engine with electric start for efficient pickup and superior performance
- 3. High lift mechanism hydraulically raise the collection bin up to 60 inches and dump to unload the contents into a garbage bin or trailer

#### STANDARD FEATURES

- All steel construction
- ·Hydraulic lift and dump
- ·Electric start engine
- •Collection boot is quickly and easily attached to the mower deck
- •Handle on hose and hose end for ease of vacuuming flower beds, etc
- Storage Stand

## Optional Accessory:

Docking Station

#### Compatibility Notes:

The RV602 collection vacuum can not The RV602 collection vacuum can not be be used on a power unit equipped with a Ventrac cab or canopy.

The RV602 collection vacuum can not be used on a 4500Z power unit equipped with a propane kit.

used on a 4500 power unit equipped with directional/hazard lights.

Recommended for use with 4100 power units serial number 4100-\*EC1501 and higher, 4200 power units serial number 4200-\*EB2555 and higher, and all 4500 power units.





